

AZ910

DSNG and Contribution Demodulator

Azimuth Product Family

AZIMUTH

SERIES

Description

The AZ910 is a state-of-the-art satellite demodulator designed for broadcast contribution, Digital Satellite News Gathering (DSNG) and Primary distribution applications over satellite in full compliance with the DVB standards.

In its default configuration, the AZ910 is capable to demodulate one MPEG transport stream in DVB-S, DVB-DSNG or DVB-S2 mode and to interface with terrestrial broadcast network through a standard ASI interface. Optionally, an optical ASI interface can be added. BISSM descrambling option can be activated to descramble Multiple program streams

To simplify the migration towards IP, the AZ910 is also available with DualFlow (combined ASI+Ethernet interface), providing broadcasters the following capabilities:

- The ability to demodulate Multistream and VCM carriers, and to output up to two transport streams and one IP stream simultaneously.
- The ability to interface (via a GbE output) with equipment or networks that accept transport streams carried over IP with the RTP protocol
- The ability to receive IP services (file transfers, VoIP, TCP services...) simultaneously or alternatively with transport stream(s). In this case the demodulator also performs the extraction of the IP packets encapsulated in MPE or XPE mode.

The AZ910 has a dual L-band input (950-2150 MHz). The active input is selected by the user and can provide DC power and frequency band selection signals compatible with most professional and commercial LNBs. Optionally, one L-band input can be replaced by an IF (50-180 MHz) input.

The AZ910 is equipped with an adaptive equalizer to compensates linear distortion of the transmission channel.

The integrated Noise & Distortion Estimator tool provides an accurate reading of the satellite link margin even in presence of non-linear distortion and allows the user to find the optimum input back-off setting very easily for 16APSK or 32APSK operation, whether or not non-linear predistortion is applied .

Key features

- DVB-S2 and DVB-DSNG/S compliant
- QPSK, 8PSK, 16APSK and 32APSK
- Data rates up to 155 Mbit/s
- Adaptive equalizer
- Noise & Distortion Estimator (NoDE) tool
- Optional DualFlow: ASI + GbE interfaces with integrated IP decapsulator
- Support of Multistream and /or VCM operation
- Optional BISSM descrambling
- Optional 10 MHz reference input/output
- ISSY compliant

Main advantages

- Lower operational cost thanks to highest bandwidth efficiency
- Fully compatible with the satellite DVB standards for a guaranteed interoperability
- High versatility and flexibility
- Future proof design combining video and IP technologies
- High compactness

Applications

- Contribution
- Primary distribution
- DSNG
- Professional signal monitoring

Related products

AZ110 Broadcast Satellite Modulator
AZ410 Broadcast Satellite Modem

AZ290 1+1 Demodulator Redundancy Switch
AZ200 Universal Switching system

Related documents

Care Pack Brochure



SHAPING THE FUTURE OF SATELLITE COMMUNICATIONS

www.newtec.eu

R5/11.2009

Specifications – AZ910(R7)



Input interface

Dual L-band input (default)

- Connector 2 x F-type (F), 75 ohms
- Return loss > 7 dB
- Level -65/-25dBm
- Frequency 950 - 2150 MHz
- Adjacent signal < (Co+7) dBm/Hz
where Co = signal level density

IF-band input (optional, replaces one L-band input)

- Connector BNC (F) - 75 ohms
- Return loss > 15 dB
- Level -55 to -15 dBm
- Frequency 50 - 180 MHz
- Adjacent signal < (Co+7) dBm/Hz
where Co = signal level density

LNB power and control

- max. current 350 mA (on selected IFL input)
- voltage 11,5 -14 V (Vertical polarization)
16 -19 V (Horizontal polarization)
& additional 22 kHz +/- 4KHz (band selection according to universal LNB for Astra satellites)
- 10 MHz reference

Demodulation

Supported modulation schemes and FEC

- DVB-S/DSNG:
Outer/Inner FEC: Reed Solomon /Viterbi
MODCODS:
QPSK: 1/2, 2/3, 3/4, 5/6, 7/8
8PSK: 2/3, 5/6, 8/9
16QAM: 3/4, 7/8
- DVB-S2:
Outer/Inner FEC: BCH/ LDPC
MODCODS:
QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
16APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
32APSK: 3/4, 4/5, 5/6, 8/9, 9/10

Baud rate range

- DVB-S2
- QPSK/8PSK/16APSK 0,256 – 45 Mbaud
- 32 APSK 1-33 Mbaud
- DVB-S/DSNG
- QPSK/8PSK/16QAM 1-45Mbaud

Frame length

- DVB-S2 Short Frames*** 16200 bits
- DVB-S2 Normal Frames 64800 bits
- DVB-S/DSNG 188 bytes

Roll-off factor

- 20 % - 25% -35%

DVB-S2 performances at PER 1E-5

Config	Short Frames		Normal Frames	
	< 15 Mbaud	< 45 Mbaud	Es/No	Es/No
QPSK- 1/3	-0,6	-0,7		
QPSK- 2/5	0,4	0,2		
QPSK- 1/2	1	1,4		
QPSK- 3/5	3,1	2,8		
QPSK- 2/3	3,8	3,6		
QPSK- 3/4	4,5	4,3		
QPSK- 4/5	5,1	5,1		
QPSK- 5/6	5,8	5,5		
QPSK- 8/9	6,7	6,6		
QPSK- 9/10	-	6,7		
8PSK- 3/5	6,5	6,3		
8PSK- 2/3	7,4	7,1		
8PSK- 3/4	8,6	8,4		
8PSK- 5/6	10,2	9,7		
8PSK- 8/9	11,4	11,1		
8PSK- 9/10	-	11,3		
16APSK- 2/3	9,9	9,6		
16APSK- 3/4	10,9	10,5		
16APSK- 4/5	11,6	11,5		
16APSK- 5/6	12,4	12,1		
16APSK- 8/9	13,6	13,3		
16APSK- 9/10	-	13,6		
32APSK- 3/4	-	13,6		
32APSK- 4/5	-	14,5		
32APSK- 5/6	-	14,9		
32APSK- 8/9	-	16,1		
32APSK- 9/10	-	16,5		

DVB DSNG/S performances at BER 1E-7 after RS

Config	< 20 Mbaud		> 20 Mbaud	
	Eb/No	Eb/No	Eb/No	Eb/No
QPSK- 1/2	3,9	3,9		
QPSK- 2/3	4,4	4,5		
QPSK- 3/4	4,9	5,1		
QPSK- 5/6	5,4	5,8		
QPSK- 7/8	5,8	6,4		
8PSK- 2/3	6,3	6,5		
8PSK- 5/6	8,3	8,8		
8PSK- 8/9	8,8	9,8		
16QAM- 3/4	8,4	8,6		
16QAM- 7/8	10,1	11,1		

Output interfaces

ASI interface (default)

- ASI (Asynchronous Serial Interface) :
- BNC (F) - 75 ohms (coax) or optionally ST (optical)
- 188 byte mode
- SPI interface
- 25 pin sub-D connector
- 188 byte mode
- BISSM: mode 0, 1 and E
BISSM does not modify PSI/SI tables. It can descramble any BISS-compliant scrambled stream, but the output will have PSI/SI tables still containing CA descriptors and CAT.
- DualFlow: Combined ASI+Ethernet (optional)
• 2 x ASI on BNC (F) - 75 ohms (coax)
• 188 byte mode
• Auto switching 10/100/1000 Base-T Ethernet interface
- Transport stream on IP interface (UDP/RTP)
- Layer 2 bridge mode: Ethernet frames over satellite (data piping)
- Layer 3 bridge or router mode: IP packets over satellite using Multi Protocol (MPE) or Extended Performance (XPE) Encapsulation
- Processing of up to 40 000 IP packets per second – maximum 50 Mbit/s
- DVB-S2 Multistream and VCM support

10 MHz reference input / output (optional)

- Connector BNC (F) – 50 ohms
- Input level -3dBm up to 7dBm
- Output level +7dBm

Internal Reference frequency

- High Stability (optional)
Stability $\pm 5 \times 10^{-8}$ over 0°C to 70°C
Ageing: ± 15 ppb/day
 ± 300 ppb/year

- Very High Stability (optional)
Stability $\pm 2 \times 10^{-9}$ over 0°C to 65°C
Ageing: $\pm 0,5$ ppb/day
 ± 500 ppb/10 year

Generic

Monitor and control interfaces

- Web based GUI
- Diagnostics report, alarm log (HTTP)
- RMCP over TCP/IP/UDP and RS232/RS485
- SNMP v2c

Alarm interface

- Electrical dual contact closure alarm contacts
- Connector 9-pin sub-D (F)
- Logical interface and general device alarm

Physical

- Very compact: 1RU, width: 19", depth 51 cm, 6 kg
- Power supply: 90-130 & 180-260 Vac, 105 VA, 47-63 Hz
- Temperature
- Operational: 0°C to 40°C
- Storage: -40 to +70°C
- Humidity: 5% to 85% non-condensing
- CE label

Ordering information

AZ 910 DSNG AND CONTRIBUTION DEMODULATOR		Order n°
Default Configuration		
DVB demodulator, SNMP Output interface: ASI Input interface: L-band (950-2150 MHz) Modulation & baud rate: DVB-S Q/8PSK, DVB-S2 Q/8PSK 45 Mbaud		AZ910
Configuration options		
Category	Max. 1 option per category	
Output Interface	ASI	Default
	ASI + Optical ASI	AP-02
Input Interface	DualFlow: Ethernet + ASI (CCM/VCM)	AP-06
	L-band	Default
	L-band + 10 MHz	AJ-02
Modulation & Baud rate	IF+ L-band	AJ-03
	IF+ L-band + 10MHz	AJ-04
Modulation & Baud rate	DVB-S/S2 Q/8PSK 45Mbaud	Default
	DVB-S/S2 Q/8PSK, 16QAM, 16APSK 45Mbaud *	AL-12
	DVB-S/S2 Q/8PSK, 16QAM, 16/32APSK 45/33Mbaud *	AL-16
Additional options		
Category	Max. 1 option per category	
10MHz reference In/Out	High stability	GR-01
	Very high stability	GR-02
Encryption	BISSM (**)	AD-02
Services		
Category	Max. 1 option per category	
Assistance	Care Pack Basic	GA-06
	Care Pack Extended	GA-07

(*) upgradeable via license key
(**) Not available with DualFlow options
(***) Short Frames not available in 32APSK

Europe

Tel: +32 3 780 65 00
Fax: +32 3 780 65 49

North-America

Tel: +1 203 323-0042
Fax: +1 203 323-8406

South-America

Tel: +55 11 2092 6220
Fax: +55 11 2093 3756

Asia-Pacific

Tel: +65 6777 22 08
Fax: +65 6777 08 87

China

Tel: +86 10-823 18 730
Fax: +86 10-823 18 731

MENA

Tel: +971 4 390 18 78
Fax: +971 4 368 67 68